




ВЫСОКОЕ ДАВЛЕНИЕ - соединители ORFS

описание	давл. [бар]	индекс (гальв. сталь)	наружный диаметр трубки		ORFS
			[мм]	[дюйм]	
Адаптер тройник L с внутр. резьбой/ наруж. резьбой ORFS  EVL	630	HO-EVL-09	6	1/4	9/16-18
		HO-EVL-11	8-10	5/16-3/8	11/16-16
		HO-EVL-13	12	1/2	13/16-16
	420	HO-EVL-16	14-15-16	5/8	1-14
		HO-EVL-19	18-20	3/4	1.3/16-12
		HO-EVL-23	22-25	7/8-1	1.7/16-12
	280	HO-EVL-27	28-30-32	1.1/4	1.11/16-12
		HO-EVL-32	35-38	1.1/2	2-12

описание	давл. [бар]	индекс (гальв. сталь)	наружный диаметр трубки		ORFS
			[мм]	[дюйм]	
Пробка с внутр. резьбой ORFS  VKA	630	HO-VKA-09	6	1/4	9/16-18
		HO-VKA-11	8-10	5/16-3/8	11/16-16
		HO-VKA-13	12	1/2	13/16-16
	420	HO-VKA-16	14-15-16	5/8	1-14
		HO-VKA-19	18-20	3/4	1.3/16-12
		HO-VKA-23	22-25	7/8-1	1.7/16-12
	280	HO-VKA-27	28-30-32	1.1/4	1.11/16-12
		HO-VKA-32	35-38	1.1/2	2-12

описание	давл. [бар]	индекс (гальв. сталь)	наружный диаметр трубки		ORFS
			[мм]	[дюйм]	
Пробка с нар. резьбой ORFS  ROV	630	HO-ROV-09	6	1/4	9/16-18
		HO-ROV-11	8-10	5/16-3/8	11/16-16
		HO-ROV-13	12	1/2	13/16-16
	420	HO-ROV-16	14-15-16	5/8	1-14
		HO-ROV-19	18-20	3/4	1.3/16-12
		HO-ROV-23	22-25	7/8-1	1.7/16-12
	280	HO-ROV-27	28-30-32	1.1/4	1.11/16-12
		HO-ROV-32	35-38	1.1/2	2-12

описание	давл. [бар]	индекс (гальв. сталь)	наружный диаметр трубки		ORFS
			[мм]	[дюйм]	
Гайка с резьбой UNF  MP	630	HO-MP-09	6	1/4	9/16-18
		HO-MP-11	8-10	5/16-3/8	11/16-16
		HO-MP-13	12	1/2	13/16-16
	420	HO-MP-16	14-15-16	5/8	1-14
		HO-MP-19	18-20	3/4	1.3/16-12
		HO-MP-23	22-25	7/8-1	1.7/16-12
	280	HO-MP-27	28-30-32	1.1/4	1.11/16-12
		HO-MP-32	35-38	1.1/2	2-12